

# VENUE: Vulkan Arena

Last update: APRIL 2026

<b>CAPACITY SOLD TICKETS</b>		800 standing // 400 seated
<b>ADDRESS</b>		Vulkan 26, 0178 Oslo
<b>GPS KOORDINATES</b>		N 59°55'20.766" E 10°45'04.109"
<b>PARKING</b>		The venue has parking for 14m nightliner. 32a 230V 3 phase. Please advance if needed. Only available after 14.00.
<b>LOAD IN</b>		A loading dock on street level. 5m push to stage. Load in is about 150m push from the bus parking.
<b>DRESSING ROOM</b>		One common room with a small kitchen with necessary equipment. Tables and chairs. One well furnished room with seating suitable for approx 10 people. One rest room with a toilet, sink and mirror. One shower room with toilet.
<b>STANDARD RUNNING TIMES</b>		Soundcheck: from 17:00 No amplified sound or drums before 17:00 or after 00:00 No haze or smoke before 17:00 Doors: 20:00 Show: 21:30 Support act (if applicable): 21:00 and 22:00 Curfew: 01:00
<b>INTERNET</b>		100/100mbps LAN for streaming at RJ45 connectors at SR, FOH floor or FOH balcony available <b>UPON REQUEST AT A COST</b> . Free WLAN for guests share the same line but are on different networks and is constricted to 2/4mbps pr guest user.
<b>STAGE</b>		Standard and maximum: 5m deep x 8m wide x 1m high (stage is built from 20 2x1m Nivtec elements) 7 stagedecks available for drum/keyboard riser etc Clearance hall floor to hall ceiling is 5,72m Clearance stage floor to light truss @ 100cm stage is 3,72m Clearance stage floor @100cm to lowest house light is 3,05m 10m barricades available
<b>FOH</b>		Positioned under balcony 11,25m from main PA and stage front at 5x8m stage.
	1 x	Midas HD96 FOH console. Software version: 2.2.5 <i>Not accepting showfiles on DOS.</i> <i>Please send both showfile and navigaton file in advance.</i>
	1 x	Midas DL251 48in/16out stagebox located on stage right. <b>NB. We enforce sound level limits at 102 LAeq over 15 minutes.</b>
<b>PA</b>	8 x	Meyer Sound Leopard Line Array elements
	2 x	Meyer Sound 1100-LFC subs
	2 x	Meyer Sound UPJ-1P outfills under balcony
	6 x	Meyer Sound UPA 1P distributed system on balcony
	2 x	Meyer sound UP Junior frontfill
	1 x	Meyer Sound Galileo Callisto 616 processing
<b>MONITOR</b>	12 x	Turbosound TMW-112 wedges
	4 x	LAB Gruppen IPD 2400 monitor amps (8 mixes)
	1 x	Turbosound B-15DP NuQ Drumfill Sub
<b>MICROPHONES &amp; DI's</b>	2 x	Shure Beta 52
	2 x	Shure Beta 91
	6 x	Sennheiser e904

	5 x	Shure SM 57	
	2 x	Sennheiser e906	
	3 x	DPA d:facto	
	6 x	Shure Beta 58a	
	2 x	DPA 2011	
	2 x	AKG C 451	
	2 x	Neumann TLM 102	
	5 x	Klark teknik DL100	
	1 x	Klark teknik DL200	
	3 x	Radial JDI	
<b>WIRELESS SYSTEM</b>		<b>The wireless system is NOT included. Available for hire only.</b>	
	1 x	Shure ULXD4Q (four channels: headset OR hand held mics)	
	4 x	Shure Beta58	
	4 x	Countryman Omni Headset COU-H6OW6LSL <i>H51 band: 534-598MHz</i>	
<b>WIRELESS FREQUENCIES</b>		Available legal frequencies for wireless equipment (max 50 mW e.r.p.)	
	K26-27	510-526 MHz	
	K31-32	550-566 Mhz	
	K35	582-590 Mhz	
	K39	614-622 Mhz	
	K46-47	670-686 Mhz	
	K-SDL	738-753 Mhz	
<b>STANDS</b>	2 x	Tall roundbase w/boom	
	12 x	Tall tripod w/boom	
	9 x	Short roundbase w/boom	
	2 x	Medium tripod w/boom	
	1 x	Short tripod w/boom	
<b>CABLES</b>	80 x	XLR-cables (3m, 5m and 10m)	
<b>LIGHTS</b>	1 x	GrandMA3 Compact Running gMA3 v.2.3.2.0 and MA2 v.3.9.61.5	
	24 x	16A Dimmer	
	36 x	1kW 1Kw PAR64	
	4 x	650W Selecon Acclaim 650w Fresnel, 6°-60°	
	1 x	Prolights Eclipse HD2 LED profile (15-30°)	
	4 x	LED Fresnel WT 150	
	2 x	650W 4-Light Blinders, Par36 120V	
	2 x	SGM X-5 Led Strobes	
	4 x	Xbar 12x12W RGBWAUV Xline	
	6 x	Martin ERA 300 Profile	
	10 x	Chauvet Rogue R2 Wash	
	1 x	MDG ATMe	
	6 x	Prolights JetBeam2 floor pack (NOT included, available for hire)	
<b>PYRO</b>		No pyro allowed at the venue du to local fire restrictions.	
<b>RIGGING</b>		Lighting rig (8m x 8m) flown by 4 × 1000kg traveling motors. Max load evenly distributed: 1840 kg Max available load for guest lights, evenly distributed: 800 kg Max available load for guest lights LX2 and LX3 400 kg 2 available rigging pionts in venue hall. Max vertical load pr. point: 800 kg	
<b>POWER</b>		Total venue production power available: 400V 140A	
		Total guest production power is 400V 50A, available on the following connectors:	
	1 x	400V 63A on 63A CEE connectors (3P-N-E) on stage right.	Free to use.
	1 x	400V 32A on 32A CEE connectors (3P+N+E) on stage right. Power distribution to 3x230V 16A on CEE 7/3 conectors (Schuko type F).	Used for backline.
	1 x	400V 32A on 32A CEE connectors (3P+N+E) on stage right. Power distribution to 3x230V 16A on CEE 7/3 conectors (Schuko type F).	Used for lighting rig.
	1 x	400V 32A on 32A CEE connectors (3P+N+E) on stage left. Power distribution to 3x230V 16A on CEE 7/3 conectors (Schuko type F).	Free to use
FOH-power	2 x	16A on CEE 7/3 conectors (Schuko type F).	

**IMPORTANT: all connectors can not run on maximum load concurrently. Please contact us to make necessary arrangements if additional power requirements exceeds 50A on 400V. An additional 400V 63A can be arranged at a cost.**

<b>AV</b>	1 x	LED screen - 6,528m x 3,072m (2176x1024 pixels ) P3 Mounted 1m up from hall floor, flush with stage floor @100cm.
	1 x	Nova Star VX6s Video Controller HDMI and 3G SDI connection on SR or FOH Max resolution from FOH is 1920x1080 (16:9). Optional uscaling to 2176x1024 (17:9) LED-screen outside venue for event branding - 1600 x 256 pixels (two short screens on each side is 320px wide and the middle screen is 960px wide)
		<b>Additional AV equipment is not included. Prices upon request:</b>
	1 x	Roland XS-1HD 4 channel matrix HDMI switcher and scaler
	1 x	PC with Powerpoint for main screen and presenter view
	1 x	MacBook Pro with Qlab

**CONNECTION**

		<b>FOH ground floor / stage right (cable run 30 meter from wall to wall)</b>
	10 x	Cat6a (SF/UTP shielded) installed in wall
	4 x	110 ohm AES/EBU/DMX, 3/5 pin f/m xlr in parallell (two in use for house lights)
	4 x	HD-SDI 3G, 75ohm, 5GHz, BNC connectors
		<b>FOH balcony / stage right (cable run 40 meter from wall to wall)</b>
	6 x	Cat6a (SF/UTP shielded) installed in wall
	2 x	110 ohm AES/EBU/DMX, 3/5 pin f/m xlr in parallell (both in use for house lights)
	4 x	HD-SDI 75ohm, 5GHz, BNC connectors

**BACKLINE**

		<i>Our backline is usually available for hire. Prices upon request.</i>
	1 x	Ampeg SVT Classic, w/6x10" cabinet
	1 x	Fender Hot Rod Deluxe (no footswitch)
	1 x	Vox AC30 CC2 (no footswitch)
	2 x	Pioneer CDJ-3000 (firmware 3.22)
	1 x	Pioneer DJM-A9 (firmware 1.19)